

US Series Ion Selective Electrode

Features

- Combination ion selective electrode
- No reference electrode needed
- Solid state sensors Ideal for unskilled operatives



Specifications

Model	Ion	Concentration (mol/L)	Limits (ppm)	pH Range	Operating Temperature
NH4-US	Ammonium	$5 \times 10^{-6} \sim 1$	0.1~18000	4~10	0~50°C
Br-US	Bromide	$5 \times 10^{-6} \sim 1$	0.4~79900	1~12	0~80°C
Cd-US	Cadmium	$1 \times 10^{-8} \sim 0.1$	0.01~11200	2~12	0~80°C
Ca-US	Calcium	$5 \times 10^{-7} \sim 1$	0.02~4000	2.5~11	0~40°C
CL-US	Chloride	$5 \times 10^{-6} \sim 1$	1.8~35500	2~12	0~80°C
Cu-US	Cupric	$1 \times 10^{-8} \sim 0.1$	0.006~6400	2~12	0~80°C
Cn-US	Cyanide	$5 \times 10^{-6} \sim 0.01$	0.2~260	10~14	0~80°C
F-US	Fluoride	$1 \times 10^{-6} \sim \text{saturation}$	0.02~saturation	5~7	0~80°C
I-US	Iodide	$5 \times 10^{-8} \sim 1$	0.06~127000	0~14	0~50°C
Pb-US	Lead	$1 \times 10^{-8} \sim 0.1$	0.2~20700	4~7	0~80°C
NO3-US	Nitrate	$7 \times 10^{-6} \sim 1$	0.4~62000	2.5~11	0~50°C
K-US	Potassium	$1 \times 10^{-6} \sim 1$	0.04~39000	2~12	0~40°C
Ag-US	Silver	$1 \times 10^{-7} \sim 1$	0.01~107900	2~12	0~80°C
Na-US	Sodium	$1 \times 10^{-5} \sim 1$	0.1~23000	>9	0~80°C
S-US	Sulphide	$1 \times 10^{-7} \sim 1$	0.003~32100	2~12	0~80°C
NH3-US	Ammonia	$1 \times 10^{-6} \sim 1$	0.02~17000	11	0~50°C

WH-UK Water Hardness Electrode

Features

- Combination water hardness electrode
- No filling solution required
- Long lifetime



Specifications

Model	WH-UK
Concentration	0.05~200mmol/L
pH Range	2~11pH
Operating Temperature	0~50°C, 32~122°F
Cable Length	1m
Connector	BNC
Dimensions	120(L)×12(Dia.)mm