

MiniT-100 Series



Product Information

The MiniT series dry bath incubator combine a microprocessor-controlled, a fast heating micro-tube block. The MiniT series are suitable for a range of uses in life science, molecular biology, environmental and industrial laboratories and a variety of applications including incubation, enzyme reactions, immuno-assays.

Features

1. LCD display. It is easy to set up and use
2. Small footprint: MiniT series are a personal sized that fits in the palm of your hand
3. Simultaneous display of set and actual time, temperature
4. Temperature deflection adjusting meet with different demands
5. Beep-signal/Stop after program completed
6. Interchangeable aluminum alloy sample blocks provide versatility and allow easy cleaning and disinfecting
7. With DC12V or DC24V power for total portability, beep-signal/stop after program completed

Technical Data

Model	MiniT	MiniT-C	MiniT-100
Temperature Control Range	RT+5°C~80°C	0°C~100°C	RT+5°C~100°C
Timing Range	1~999min or 1~999sec	1~999min or 1~999sec	1~999min or 1~999sec
Temp. Control Accuracy	±0.5°C	±0.5°C	±0.5°C
Display Accuracy	±0.1°C	±0.1°C	±0.1°C
Heating Time(25°C to Max.Temp.)	≤12min	≤20min	≤15min
Cooling Time(25°C to 0°C)	—	≤25min (*)	—
Temp. Control Accuracy @40°C	±0.3°C	±0.3°C	±0.3°C
Heating Lid	—	—	—
Heating Lid Temperature Range	—	—	—
Dimension(L x W x H) mm	150 x 110 x 100	162 x 110 x 140	152 x 120 x 112
Net Weight / Power	0.5kg / DC12V	1.0kg / DC12V	0.8kg / DC24V