

DLAB Microplate Mixer is used for holding single or double microplates. The compact shape of MX-M Microplate Mixer occupies less bench space and makes the storage easier. It is widely used in life sciences including microbiology, cell and molecular biology, immunology and biotechnology.

## MX-M Microplate Mixers

### Features

- A wide range of speed from 0 to 1500rpm
- Used for various mixing applications with optional adapters
- Maintenance-free brushless DC motor



Brushless DC motor



Wide range of accessories



### PS1.2 Microplate clamp(Default)

Cat. No.18900042



### PS1.1 Universal top plate

Used with tube adapters

Cat. No.18900067



### VT1.3.1 tube adapter

for 48 holes test tubes, Ø6mm

Cat. No.18900020



### VT1.3.2 tube adapter

for 15 holes test tubes, Ø10mm

Cat. No.18900021



### VT1.3.3 tube adapter

for 12 holes test tubes, Ø12mm

Cat. No.18900022



### VT1.3.4 tube adapter

for 8 holes test tubes, Ø16mm


Cat. No.18900023



### VT1.3.5 tube adapter

for 8 holes test tubes, Ø20mm

Cat. No.18900024



### MXM-116

Double microplate clamps

Cat. No.18900079

### Specifications

	MX-M
Shaking movement	Orbital
Orbital diameter	4.5mm
Max. shaking weight (with accessory)	0.5kg
Motor type	Brushless DC motor
Motor rating input	18W
Motor rating output	10W
Speed range	Single microplate: 0-1500rpm Double microplate: 0-1000rpm
Speed display	Scale
Voltage	100-240V,50/60Hz
Power	20W
Dimension	260×150×80mm
Weight	3kg
Permissible ambient temperature and humidity	5-40°C,80%RH
Protection class	IP21