

Thermostatic Water Baths

○ Used for precision constant temperature and auxiliary.



Characteristics:

- SHHW21.420All model cover for the two holes water bath, can be used as a digital two holes water bath.
- SHHW21.600All model cover for the six holes water bath, can be used as a digital six holes water bath.

Main Technical Parameters:

Model		HHW21.420All	SHHW21.420All	HHW21.600All	SHHW21.600All
Function	Tem. Range	RT+5 ~ 65℃	RT+5 ~ 100℃	RT+5 ~ 65℃	RT+5 ~ 100℃
	Tem. Resolution Ratio	0.1℃			
	Tem. Motion	± 0.5℃			
	Tem. Uniformity	± 1.0℃			
Structure	Inner Chamber	High quality hairline stainless steel plate			
	Outer Shell	Cold rolling steel electrostatic spraying exterior			
	Cover	High quality hairline stainless steel plate			
	Cover circle	Without	With	Without	With
	Test tube rack	Without	With	Without	With
Controller	Heater	Stainless steel heating tube			
	Power Rating	0.5kW	1kW	0.75kW	2kW
	Tem. control mode	PID			
	Tem. setting mode	Touch button setting			
	Tem. display mode	Measuring temperature: display on the three digital tubes upper row ; setting temperature: display on the lower row			
	Timer	0 ~ 9999min (with timing wait function)			
	Operation function	Fixed temperature operation, timing function, auto stop.			
	Program function	No			
	Additional function	Deviation correction、 Menu key lock、 Power-off compensation、 Power failure memory			
	Sensor	CU50			
Safety device		Over temperature alarm			
Specification	Sink size(W*L*H)(mm)	420*180*140		600*300*200	
	Exterior size (W*L*H)(mm)	570*230*270		750*350*360	
	Packing size (W*L*H)(mm)	670*320*335		860*460*380	
	Volume	11L		36L	
	Supply (50/60Hz) Current rating	AC220V/2.3A	AC220V/4.5A	AC220V/6.8A	AC220V/9.1A
	NW/GW (kg)	8/9.5	8.5/10	17/19	18/20
Optional accessories		No			