

XSP-500E



技术参数 Specification		型号 Model			
		XSP-500D	XSP-500E	XSP-500SM	XSP-500V
Objective	4X、10X、40X(弹簧)、100X(弹簧、油) 4X、10X、40X(S)、100X(S、Oil)	•	•	•	•
目镜 Huygens eyepiecesng head	大视场目镜: WF10X、(WF16X选购件) Wide Field Eyepiece:WF10X、(WF16X optional)	•	•	•	•
观察头 Viewing head	单目头,30°倾斜 Monocular,Inclined at 30°	•			
	铰链式双目头,30°倾斜 Compensation Free Binocular Head Inclined at 30°		•		
	三目头 Trinocular head			•	
	示教头 Dual viewing head, one tube 30°,inclined and another tube vertical,360°rotatable				•
载物台 Stage	双层活动平台;平台尺寸120X125mm Double Layer Mechanical Stage, Size 120X125mm	•	•	•	•
调焦 Focusing	同轴粗微调,调焦范围30mm,微调格值0.002mm Coaxial Coarse and Fine Adjustment,Focusing Range 30mm, Focusing Interval 0.002mm	•	•	•	•
聚光镜 Condenser	NA=1.25阿贝聚光镜带可变光栏和滤色片 Abbe NA=1.25 with Iris Diaphragm&Filter	•	•	•	•
照明系统 Illumination	LED 1W灯220V或110V(卤素灯6V/20W选配, LED 3W选配) LED(1W) Lamp 220V or 110V;(LED 3W lamp optional, Halogen bulb 6V/20W optional)	•	•	•	•