NEW

DTD Series ULTRASONIC CLEANER

ULTRASONIC CLEANER

FEATURES

- Equipped with a special stainless steel basket, reduce sound cover
- The shell and cover are made by stainless steel
- The equipment controlled by Single-chip controller
- The lastest working parameters can be stored in
- memory after power-off
- Digital setting ultrasonic cleaning time
- Working time countdown display
- Display actual temperature of the cleaning tank
- Temperature setting Range: room temperature--80°C
- Timing Range: 1-99 minutes adjustable

TECHNICAL PARAMETERS

Model	Inner tank (mm)L/W/H	Volume L	Frequency KHz	Ultrasonic power W	Heating power W	Temperature adjustable °C	Time adjustable min	Drainage	Rack
SB-100DTD	300*150*100	4.5	40	100	200	RT+5-80	1-99	/	√
SB-120DTD	240*140*100	3	40	120	200	RT+5-80	1-99	/	√
SB-120DTD	240*140*150	5	40	120	200	RT+5-80	1-99	/	√
SB-3200DTD	300*155*150	6	40	180	400	RT+5-80	1-99	/	√
SB-5200DTD	300*240*150	10	40	240	800	RT+5-80	1-99	√	√
SB-5200DTD	300*240*150	10	40	360	800	RT+5-80	1-99	√	√
SB-4200DTD	300*240*200	14.4	40	400	800	RT+5-80	1-99	√	√
SB25-12DTD	500*300*150	22.5	40	500	1000	RT+5-80	1-99	√	√
SB25-12DTD	500*300*150	22.5	40	600	1000	RT+5-80	1-99	√	√
SB-800DTD	500*300*200	30	40	800	1000	RT+5-80	1-99	√	√
SB-1000DTD	600*300*300	54	28	1000	3000	RT+5-80	1-99	√	√
SB-1200DTD	600*400*300	70	28	1200	4000	RT+5-80	1-99	√	√
SB-1500DTD	600*500*300	90	28	1500	4000	RT+5-80	1-99	√	/
SB-1800DTD	600*600*300	108	28	1800	4000	RT+5-80	1-99	√	/
SB-2000DTD	User offer size	117	28	2000	6000	RT+5-80	1-99	√	/
SB-3600DTD	User offer size	207	28	3600	8000	RT+5-80	1-99	√	/

Notice :With the heating function of the ultrasonic cleaner, after heating the temperature than the actual display temperature 2-8 °C for thermostatic ultrasonic , optional ultrasonic thermostatic ultrasonic cleaner .