

INCUBATOR

Biochemical Incubator

- ♦Microprocessor control temperature and timer
- ♦LED display temperature and running timer
- ♦Stainless steel inner, with door lock.
- ♦The glass door is convenient for observation.
- ♦Over temperature alarm,
- ♦Automatic alarm after operation.
- ♦BOD culture (optional interior with socket)



Illumination Incubator

- ♦Thermostatic equipment with lighting.
- ♦Microprocessor control temperature and timer
- ♦LED display temperature ,speed and timer
- ♦Stainless steel inner, with door lock.
- ♦The glass door is convenient for observation.
- ♦Over temperature alarm
- ♦Automatic alarm after operation
- ♦Used in animalcule histolytic cultivation

Blood Bank Refrigerator

- ♦Microprocessor control temperature and deepfreeze timer , PID self-tuning
- ♦Independent high-low temperature alarm with adjustable alarm range, safe and reliable
- ♦Stainless steel inner, with door lock.
- ♦The glass window is convenient for observation.
- ♦High and low temperature alarm
- ♦Suit for the medical and health institutions, blood centers departments to store blood
- ♦Suit for cold preservation of medicine



• BLX-150/250

• BLX-50/80



Pharmaceutical Refrigerator

- ♦Microprocessor control temperature and deepfreeze timer
- ♦Independent high-low temperature alarm with adjustable alarm range, safe and reliable
- ♦Stainless steel inner, with door lock.
- ♦The glass window is convenient for observation.
- ♦High and low temperature alarm
- ♦Suit for cold preservation of medicine

Model	SPX-50B SPX-50C	SPX-80B SPX-80C	SPX-150B SPX-150C	SPX-250B SPX-250C	SPX-500B SPX-500C
Capacity	50L	80L	186L	250L	500L
Heating power	100W	100W	142W	242W	350W
Compressor power	124W	124W	200W	200W	800W
Temperature accuracy	±0.5°C	±0.5	±1°C	±1°C	±1°C
Temperature range			5-60°C		
Timer			0-9999min		
Voltage			220V 50Hz		
Dimension(mm)	480x570x920	480x570x950	550x530x1540	610x540x1700	900x710x1830
Package(mm)	580x630x1140	580x630x1180	650x620x1640	710x650x1800	1000x810x1900
G.W./N.W.	46/36kg	48/38kg	88/60kg	105/70kg	220/165kg

*Remark: SPX- C Series with LCD display temperature and time.

Model	SPX-150G	SPX-250G	SPX-300G	SPX-600G
Capacity	186L	250L	300L	600L
Temperature range	No illumination 5-50°C	with illumination 10-50°C		
Temperature accuracy	±0.5°C	±0.5°C	±1°C	±1°C
Heating power	100W	142W	800W	1200W
Compressor power	124W	200W	200W	320W
Illumination	≥2500Lux	≥2500Lux	12000Lux	12000Lux
Timer	0-9999min	0-9999min	0-9999min	0-9999min
Voltage	220V 50Hz	220V 50Hz	220V 50Hz	220V 50Hz
Dimension(mm)	550x530x1540	610x540x1700	680x660x1690	900x800x1850
Package(mm)	650x620x1640	710x650x1800	770x750x1820	1000x900x1920
G.W./N.W.	92/64kg	113/78kg	150/110kg	240/175kg

Model	BLX-50	BLX-80	BLX-150	BLX-250
Capacity	50L	80L	186L	250L
Temperature range	0-8°C	0-8°C	0-8°C	0-8°C
Temperature accuracy	±0.5°C	±0.5°C	±1°C	±1°C
Power	200W	200W	300W	400W
Timer	0-9999min	0-9999min	0-9999min	0-9999min
Voltage	220V 50Hz	220V 50Hz	220V 50Hz	220V 50Hz
Dimension(mm)	480x570x920	480x570x950	550x540x1470	600x560x1640
Package(mm)	580x630x1140	580x630x1180	650x620x1640	710x650x1800
G.W./N.W.	49/39kg	54/44kg	95/68kg	113/78kg

Model	YLX-150B	YLX-250B
Capacity	180L	250L
Temperature range	2-8°C	2-8°C
Temperature accuracy	±1°C	±1°C
Power	300W	400W
Timer	0-9999min	0-9999min
Temperature alarm range	upper limit 5-19°C, lower limit 0-5°C	upper limit 5-19°C, lower limit 0-5°C
Voltage	220V 50Hz	220V 50Hz
Dimension(mm)	550x540x1470	600x560x1640
Package(mm)	620x650x1640	650x710x1800
G.W./N.W.	95/68kg	110/78kg