



## Class II A2 Biological Safety Cabinet



**LCD Display**  
Large LCD display is easy to monitor all the safety parameters at a glance; and ergonomically sized control panel improves users interface.



**Front Window**  
Two-layer laminated toughened glass>5mm, anti UV



**Footmaster Caster**  
Universal caster with brake and leveling feet.




**SS Water Tap & Gas Tap**



**Waterproof Socket**



**Work Zone**  
Unibody design



**UV Lamp**  
Emission of 253.7 nanometers for most efficient decontamination.

## ADVANTAGE

1. Motorized front window.
2. Large LCD display, all information displayed.
3. Automatic air speed adjustable with filter block.
4. With memory function in case of power-failure.
5. Side & back wall is made of single piece stainless steel.
6. Interlock function: UV lamp and front window; UV lamp and blower, fluorescent lamp; Blower and front window.
7. Front 10° slanted to offer operator comfort while working for long time, reduce glare and maximize reach into the work area.

## TECHNICAL PARAMETERS

Model		11235BBC86(3')	11236BBC86(6')
External Size(W*D*H)		1087*775*2265mm	1873*775*2295mm
Internal Size(W*D*H)		910*600*660mm	1700*600*660mm
Work Surface Height		750mm	
Max Opening		520mm (21")	550mm (22")
Tested Opening		Safety height 200mm (8")	
Airflow Volume	Inflow	348m³/h (205cfm)	649m³/h (382cfm)
	Downflow	65%: 649m³/h (382cfm)	60%: 1212m³/h (713cfm)
	Exhaust	35%: 348m³/h (205cfm)	40%: 649m³/h (382cfm)
Front Window		Motorized. Two-layer laminated toughened glass ≥5mm. Anti UV	
HEPA Filter		Two, 99.999% efficiency at 0.3µm, filter life indicator	
Filter Guard Type		Aluminum alloy frame	
Noise		NSF 49≤61dB / EN 12469≤58dB	
Illumination		≥1000Lux	
Display		LCD Display	
Waterproof Socket		Two, Total consumption: ≤500W	
Tap		Water tap*1, Gas tap *1	
Ground Resistance		≤ 0.10Ω	
Power Supply		AC220V±10%, 50/60Hz; 110V±10%, 60Hz, Full load Amps: 9A, BTU/Hr: 1689	
Consumption		300W	500W
Alarm		Abnormal airflow velocity; Filter replacement; Front window at unsafe height	
DC Motor		One ECM motor, 110V&220V acceptable, Speed adjustable, high efficiency and low power consumption	
Material		Working area: 304 stainless steel Frame and Decorative Plate: cold-rolled steel with anti-bacteria power coating	
UV Lamp		18W	40W
		Germicidal UV lamp, Emission of 253.7 nanometers for most efficient decontamination	
Illuminating Lamp		10W*2	22W*2
		LED lamp	
Standard Accessory		Illuminating lamp, UV lamp*2, Base stand, SS water & gas taps, Drain valve, Waterproof sockets, Stainless Steel I.V. Bar with 10 hooks	
Optional Accessory		Armrest, Airflow tester, Formalin fumigation sterilizer, Infrared sterilizer, Remote control, Electric height adjustable base stand	
Package Size (W*D*H)		1220*1000*1840mm	2020*1080*1900mm
Gross Weight		270kg	363kg