

Rocker

>>> KJMR-III Multifunction Rotator

Features:

- Three selectable mixing program modes, suitable for mixing blood samples, urine, injections, plasma, and other substances.
 - Driven by an efficient DC stepper motor, it operates smoothly with low noise and has a long service life.
 - Specially designed silicone ring fixture, suitable for various types of test tubes and centrifuge tubes.
- Compact structure, less space occupation, suitable for a variety of places
- Digital control of time and speed for more precise control.
 - LCD liquid crystal display for speed, time, and operating mode, facilitating easy reading and operation.
 - Touch-sensitive membrane switch panel design for easier operation.

Technical Data:

Operation method:	Rotation: 360°clockwise 360°anticlockwise 360°clockwise-anticlockwise cross Shaking: Forward-backward reciprocating action with < 5°angle Vortex: Forward-backward reciprocating action with < 5°angle+360°clockwise rotation
Speed range:	5-40rpm
No.1 working plate:	1.5mL-15mL test tube or centrifuge tube 22pcs
No.2 working plate:	50mL centrifuge tube 6pcs, 1.5mL-15mL test tube or centrifuge tube 4pcs
Running mode:	Timing
Timing range:	1min-60h
Input voltage(frequency):	AC 220V±10%(50/60Hz)
Input power:	15W
Protective class:	IP31
Permissible ambient temperature:	5-50°C
Permissible relative moisture:	80%
Dimensions:	380×182×190mm
Net. Weight:	3 kg



Working plate 1:

Suitable for holding Ø12, Ø13, Ø16 test tubes and all types of centrifuge tubes between 1.5 mL and 15 mL.

KJMR-III



Working plate 2:

Suitable for holding Ø12, Ø13, Ø16 test tubes and all types of centrifuge tubes between 1.5 mL and 50 mL.