

Heating Incubator



Microprocessor controller (with timing function)

Summary:

Provided as a necessary equipment for scientific research to colleges as well as biological, agricultural and scientific research departments for storage of mould and biology cultivation.

Features:

- Microprocessor controller (with timing function)
- With inner glass door for easy observation.
- Polished stainless-steel chamber
- Independent temperature-limiting alarm system ensures experiments run safely.(Option)
- Printer connector and RS485 connector are options which can connect printer and computer to record the parameters and the variations of temperature. (Option)



Specifications

Model	DHP-9012 DHP-9012B	DHP-9032 DHP-9032B	DHP-9052 DHP-9052B	DHP-9082 DHP-9082B	DHP-9162 DHP-9162B	DHP-9272 DHP-9272B	DHP-9402 DHP-9602 DHP-9902
Electrical Requirement	220V 50Hz						
Temperature Range	RT+5~65℃						
Display Resolution	0.1℃ /±0.5℃						
Ambient Temperature	+5~35℃						
Power consumption	250W	200W	300W	400W	600W	750W	1100W 1400W 2200W
Chanber Volume	16L	35L	50L	80L	160L	270L	420L 620L 1000L
Interior Dimension(W×D×H)mm	250×260×250	340×320×320	415×360×355	500×400×400	500×500×650	600×600×750	640×585×1355 840×600×1355 1000×600×1600
Exterior Dimension(W×D×H)mm	530×480×420	620×490×490	690×500×500	780×530×560	790×630×810	890×740×910	780×750×1880 980×800×1880 1140×800×2150
Shelves	2(pcs)						3(pcs)/4(pcs)/4(pcs)
Timing Range	1~5999min						

Options:

- UV Sterilizer



- Printer



- Independent temperature-limiting Alarm system



- RS485 connector

